

UNCLASSIFIED

AD NUMBER	
AD008839	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited.	
FROM: Distribution authorized to DoD only; Administrative/Operational Use; JAN 1953. Other requests shall be referred to Naval Sea Systems Command, Washington, DC 20362. Pre-dates formal DoD distribution statements. Treat as DoD only.	
AUTHORITY	
NAVSEA ltr dtd 1 Apr 1968; NAVSEA ltr dtd 1 Apr 1968	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD _____

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS
DCD DIR 5200.10



UNCLASSIFIED

THIS REPORT HAS BEEN DECLASSIFIED
AND CLEARED FOR PUBLIC RELEASE.

DISTRIBUTION A
APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

CONFIDENTIAL

SECURITY INFORMATION

**VARIAN ASSOCIATES
ENGINEERING REPORT**

COPY NO. 11
JANUARY 1953

PROGRESS REPORT

DEVELOPMENT OF KLYSTRON

OSCILLATORS V-39 AND V-40

For Period: 1 October to 31 October 1952

Prepared for

Bureau of Ships

Navy Department


on


**BUSHIPS CONTRACT NObsr-52105
Index No. NE 110244**


Prepared by:

Stuart Hennies

Approved by:


H. Myrl Stearns
Vice-Pres. and Gen. Manager


Sigurd F. Varian
Vice-Pres. for Engineering


John W. Clark
Sales Manager

Page 1 of 10

NOTICE:

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18 U. S. C., Sections 793, 794, 795. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

PURPOSE

The purpose of the program engaged under BuShips Contract No. N0bsr-52105 is to design and develop two wide-range klystron oscillators, V-39 and V-40, which will comply with the specifications outlined in this contract.

The two oscillators will cover the frequency band from 10 to 21 kmc. One tube will tune over the lower half of the band from 10 to 15.5 kmc, and the other will cover the band from 15 to 21 kmc. Preliminary design tubes of each type, complete with electrical test and characteristic data, will be furnished. In addition, five tubes embodying the final design of each type will be supplied, along with electrical characteristics and test data, final proposed specifications, and manufacturing drawings.

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

PROGRESS

During the period covered by this report, the first single plunger, externally tuned tube to cover approximately the frequency range of the V-39 tube was constructed. This tube, shown in Figure 1, was built along the lines of the Varian type V-52 tube (BuShips Contract NObsr-52503). It is a two-window tube, with one of the windows almost as wide as the inside diameter of the tube cavity. This window is coupled to a section of WR-75 waveguide which contains a shorting plunger to tune the tube. The other window is smaller and is used to couple energy to the output waveguide. The half-cavity within the tube is 0.436 inch in diameter and 0.051 inch high. The drift tube is 0.080 inch in diameter.

The tube is designed with an electron gun that has a perveance of approximately 1.5. The tube normally operates at a beam voltage of 750 volts and beam current of 26 ma. In addition, the cathode and reflector have focus rings, the voltage of which can be varied independently to optimize the power output. For the data taken, the reflector focus ring was adjusted for optimum power and the cathode focus ring was at cathode potential. The tube, waveguide portion of cavity, shorting plunger, and tuner used in these measurements are shown in Figures 2 and 3.

This tube initially tuned over a range of 10.3 to 18.6 kmc using various cavity modes and reflector modes. From the data obtained, the cavity and reflector modes were identified. A power of at least 25 mw was obtained over the frequency range from 10.6 to 17.0 kmc, using the 3-3/4 and 4-3/4

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

cycle reflector modes and the full-wave cavity mode. In the 3-3/4 cycle reflector mode, 60 mw power output was obtained at 12.4 kmc, and in the 4-3/4 cycle mode, 55 mw was obtained at 15.0 kmc. Power output and tuning curves are shown in Figures 4 and 5 respectively.

Work on the tube with the 0.080-inch drift space and re-entrant reflector shell mentioned in the previous report¹ has been suspended in this program, pending performance results from tubes now under test. Meanwhile, this tube is being investigated under the development program for the V-33 tube (Contract DA 36-039 sc-149).

- - - - -

- 1 Varian Associates Engineering Report, NObsr-52105, 1 September to 30 September 1952.

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

PROGRAM FOR NEXT INTERVAL

In November, additional tests will be performed on the tube completed this month. A second tube, similar to this tube, will also be constructed. The latter tube will have, in addition to the focus ring on the cathode and reflector, a cathode which can be moved to center the beam and change the perveance.

Actual expenditures during October 1952:	\$4,625.68
Actual man-hours during October 1952:	419

Page 5 of 10

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL
SECURITY INFORMATION



FIGURE 1
FIRST SINGLE PLUNCER, EXTERNALLY TUNED V-39 TUBE

CONFIDENTIAL
SECURITY INFORMATION




FIGURE 2
SINGLE PLUNGER V-39 TUBE WITH WAVEGUIDE PORTION OF CAVITY, SHORTING PLUNGER, AND TUNER

CONFIDENTIAL
SECURITY INFORMATION




FIGURE 3
ASSEMBLED V-39 TUBE, WAVEGUIDE PORTION OF CAVITY, SHORTING PLUNGER, AND TUNER

CONFIDENTIAL
SECURITY INFORMATION

CONFIDENTIAL
SECURITY INFORMATION

Beam Voltage = 750 v




FIGURE 4
POWER OUTPUT vs. FREQUENCY
FOR SINGLE PLUNGER V-39 TUBE

Page 9 of 10

CONFIDENTIAL
SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION




FIGURE 5
TUNING CURVE FOR SINGLE PLUNGER V-39 TUBE

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

Contract No. NObsr-52105(1733)- Index No. NE 110244

25 130

Subject: Development of Two Wide Range Reflex Oscillator Tubes V-39, V-40

DISTRIBUTION LIST

<u>Copy No.</u>	<u>Quantity</u>	<u>Address</u>
1 - 2	2	Evans Signal Laboratory Belmar, New Jersey Attn: Thermionics Branch
3 - 4	2	Bureau of Ships Department of the Navy Washington, D.C. Attn: Code 836
5 - 7	3	Naval Research Laboratory Anacostia Station Washington 20, D.C. Attn: Code 2000
8	1	Naval Research Laboratory Anacostia Station Washington 20, D.C. Attn: Code 3940
9	1	Commanding Officer Watson Laboratories Red Bank, New Jersey Attn: WLEOP-1A
10 - 11	2	Commanding General Wright Air Development Center Attn: WCES02 Wright-Patterson Air Force Base, Ohio
12	1	Panel on Electron Tubes Room 601 - 139 Centre Street New York 13, New York Attn: A. Lederman, Secretary
13	1	National Bureau of Standards Washington 25, D.C. Attn: J. E. White

Page 1 of 2

25 130

CONFIDENTIAL

SECURITY INFORMATION

CONFIDENTIAL

SECURITY INFORMATION

Contract No. N0bsr-52105(1733) - Index No. NE 110244

Subject: Development of Two Wide Range Reflex Oscillator Tubes V-39, V-40

DISTRIBUTION LIST

<u>Copy No.</u>	<u>Quantity</u>	<u>Address</u>
14 - 15	2	Bureau of Aeronautics Department of the Navy Washington 25, D.C. Attn: SEL-54
16 - 17	2	Director U.S. Naval Electronics Laboratory San Diego 52, California Attn: M. H. Attebury
18 - 21	4	Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 816
22	1	Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 838
23 - 24	2	Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 834
25	1	Inspector of Naval Material P.O. Box 3364 San Francisco 19, California
26 - 27	2	U.S. Atomic Energy Commission Division of Construction & Supply Washington, D.C. Attn: Mr. F.M. Womeldorff
28	1	Documents Room Project Lincoln (MIT) P.O. Box 390 Cambridge 39, Massachusetts Attn: Ethyl R. Branz
29 - 32	4	Retained for use by Varian Associates

Page 2 of 2

CONFIDENTIAL

SECURITY INFORMATION